

IN THE CLAIMS

Please amend the claims as follows:

Claims 1-24 (Canceled):

Claim 25 (Currently Amended) A process ~~[[of]]~~ for producing a compound ~~including~~ comprising:

(A) introducing a substrate and a reaction medium into a reactor at a reaction step of ~~undergoing reaction in a reactor under~~ a pressure higher than atmospheric pressure and at a temperature at least equal to the ~~the~~ [[a]] boiling point at atmospheric pressure of ~~the~~ [[a]] the reaction medium ~~or higher, for a time and under conditions suitable~~ to form [[a]] said compound in the form of a slurry containing the compound and the reaction medium;

(B) separating ~~separation step of separating a fixed amount or more at least some of~~ the reaction medium from [[a]] said slurry at ~~containing the compound and the reaction medium under~~ a pressure higher than atmospheric pressure and at a temperature ~~[[of a]] at~~ least equal to the boiling point at atmospheric pressure of the reaction medium ~~or higher in a separation device, to obtain a cake having a weight ratio of a cake-attached liquid of not more than 50 % based on the solids content; and~~

(C) [[a]] drying ~~[[step of moving]]~~ the resulting cake by moving it into a compound recovery zone under conditions in which the internal energy released by the movement of the compound into the compound recovery zone evaporates the cake-attached liquid, said conditions comprising moving the compound into a compound recovery zone having a pressure lower than the pressure in (B) ~~the separation device, thereby evaporating the cake-attached liquid by internal energy released by the movement.~~

Claim 26 (Currently Amended) The process according to claim 25, wherein in the drying step (C), the resulting cake is moved into a compound recovery zone having a pressure

Appl. Serial No.: 10/713,013

In reply to Official Action of February 22, 2006

lower than the pressure in ~~the separation device~~ (B) and a temperature lower than the temperature in (B) ~~the separation device~~.

Claim 27 (Previously Presented): The process of producing a compound according to claim 25, wherein in the separation step (B), the cake is washed with a washing liquid having an evaporation latent heat at the boiling point at atmospheric pressure of not more than 300 kcal/kg in a state in which the pressure is kept at higher than atmospheric pressure, and the temperature is kept at the boiling point at atmospheric pressure of the reaction medium or higher.

Claim 28 (Previously presented): The process of producing a compound according to claim 25, wherein the reaction medium has an evaporation latent heat at the boiling point at atmospheric pressure of not more than 300 kcal/kg.

Claim 29 (Previously Presented): The process of producing a compound according to claim 25, wherein in the separation step (B), the cake is washed with a washing liquid having a temperature in the range of the boiling point at atmospheric pressure of the washing liquid or higher but not higher than $(TB1 + 100\text{ }^{\circ}\text{C})$ (wherein TB1 stands for the temperature ($^{\circ}\text{C}$) of an unwashed cake).

Claim 30 (Previously Presented): The process of producing a compound according to claim 25, wherein in the separation step (B), the cake is washed with a washing liquid in an amount of from 0.03 to 5.0 times based on the weight of the solids content in the cake.

Claim 31 (Previously Presented): The process of producing a compound according to claim 25, wherein the compound to be formed in the reaction step (A) is an aromatic carboxylic acid.

Claim 32 (Previously Presented): The process of producing a compound according to claim 31, wherein the aromatic carboxylic acid is terephthalic acid.

Claim 33 (Previously Presented): The process of producing a compound according to claim 31, wherein in the reaction step (A), an alkyl group-substituted aromatic compound is subjected to liquid phase oxidation with molecular oxygen to obtain the aromatic carboxylic acid.

Claim 34 (Currently Amended): The process of producing a compound according to claim 32, wherein in ~~the reaction step~~ (A), p-xylene is subjected to liquid phase oxidation with molecular oxygen to obtain terephthalic acid.

Claim 35 (Currently Amended): The process of producing a compound according to claim 25, wherein ~~the reactions step~~ (A) is carried out at a temperature in the range of from 50°C to 350°C.

Claim 36 (Currently Amended): The process of producing a compound according to claim 25, wherein ~~the reactions step~~ (A) is carried out under a pressure in the range of exceeding atmospheric pressure but not higher than 20 MPa.

Claim 37 (Currently Amended): The process of producing a compound according to claim 25, wherein in the drying step (C), a difference between the temperature of the cake in (B) ~~within the separation device~~ and the temperature of the cake discharged into the compound recovery zone is from 5°C to 250°C.

Claim 38 (Currently Amended): The process of producing a compound according to claim 25, wherein in the drying step (C), a difference between the pressure in (B) ~~within the separation device~~ and the pressure in the compound recovery zone is from 0.01 MPa to 22 MPa.

Claim 39 (Previously Presented): The process of producing a compound according to claim 25, wherein in the drying step (C), the compound to be discharged has a median diameter of from 40 µm to 300 µm.

Claim 40 (Previously Presented): The process of producing a compound according to claim 25, wherein in the drying step (C), a weight ratio of the cake-attached liquid is not more than 10 % based on the solids content.

Claim 41 (Previously Presented): The process of producing a compound according to claim 25, wherein in the drying step (C), a weight ratio of the cake-attached liquid is reduced by 3 % or more based on the solids content.

Claim 42 (Currently Amended): The process of producing a compound according to claim 25, wherein in the drying step (C), an intermediate chamber is provided between a separation device used for (B) and the compound recovery zone.

Claim 43 (Currently Amended): The process of producing a compound according to claim [[25]] 42, wherein in the drying step (C), a dry gas is introduced into the intermediate chamber and/or the compound recovery zone.

Claim 44 (Previously Presented): The process of producing a compound according to claim 25, wherein in the drying step (C), the pressure in the compound recovery zone is atmospheric pressure.

Claim 45 (Currently Amended): The process of producing a compound according to claim 25, wherein ~~in the drying step (C)~~, a pressure drying device provided with a discharge valve is used for drying step (C).

Claim 46 (Currently Amended): The process of producing a compound according to claim 45, wherein a contact portion between a valve body and a valve seat of the discharge valve is linear[.,] and its shape is circular.

Claim 47 (Previously Presented): The process of producing a compound according to claim 45, wherein in the drying step (C), the discharge valve is intermittently opened, and an opening time is from 0.01 seconds to 1 second.

Claim 48 (Previously Presented): The process of producing a compound according to claim 25, wherein an intermediate processing step (D) for carrying out crystallization or dissolution of the compound is provided between the reaction step (A) and the separation step (B).

Appl. Serial No.: 10/713,013
In reply to Official Action of February 22, 2006

Claim 49 (Previously Presented): The process of producing a compound according to claim 25, wherein in the reaction step (A), the formed compound is obtained as a solid.